



ARNO X

Integrated Amplifier

ARNO X

Integrated Amplifier



Technical specifications





ARNO X

Integrated Amplifier

ARNO X

Integrated Amplifier



- *Hybrid stereo integrated amplifier (2 X 18W)*
 - *Fully dual mono power supply with common ground in Y*
 - *regulated and filtered symmetrical power supply for the tube*
 - *Switching relays and remote control have separate ground from the signal's one*
 - *Printed circuit board suspended and damped by silent blocks*
 - *Double triode tube (ECC88)*
 - *Texas Instruments transistor LM1875T*
- *Aluminium case*
- *EMI/RFI Shielding*
- *Motorized ALPS Potentiometer (RK27 - Blue Velvet)- Remote control*
- *Double custom audio grade toroidal transformer (very low induction noise) - Stainless steel box*
- *Furutech IEC Plug / Schurter fuse*
- *3 input lines (RCA sockets)*
- *1 speakers out (binding post)*
- *Size : 25 x 25 x 18 (cm) - (excl. buttons & connectors)*
- *Color ; black / white*
- *Option : other finishes to choose from*
 - *Painting*
 - *Powder coating*
- *Measurements :*
 - *Input impedance : 100Kohms*
 - *Power : 2 x 18W (8 ohms) - 2 x 20W (4 ohms)*
 - *Bandwidth : 20Hz - 50Khz (-1dB) at max power*
- *Entirely manufactured in France (components soldering and internal cabling)*

